

Product Specifications

SOLAR LED FLOOD LIGHT
Powered by ZeroSUN™ Solar Controller

20W-40W-50W
5 YEAR Warranty



Model: HT Series 20/40/50W

130LPW

50,000 hrs

SIGN LIGHTING and AREA LIGHTING applications

Overview

Luminous efficacy >130LPW

Plug-and-Play - Simple Connections

LED: Lumileds 3030

MC4 connector and Cable, 2m long (STANDARD)

Light with heavy duty Trunnion Bracket

Integral Battery and Controller

Batteries kept warm during winter months

Operating Temperatures: -30 to +55C

Power Factor >0.9



MC4 Connector & Cable, 2m long
Custom Cable length is available

Model	Watts	Lumens
ZA-HT20W12V	20	2600
ZA-HT40W12V	40	5200
ZA-HT50W12V	50	6500

ZA-HT20W12V 20 **2600**

ZA-HT40W12V 40 **5200**

ZA-HT50W12V 50 **6500**

Connectors: MC4 quick connect

Trunnion Mount



Photometric

CRI Ra>75

Color 5700K

Beam Angle: 140/70°

Measurements/Weight

Luminaire: 6.5x5.6x1.5" / 13.0/14.0/15.0lbs

PV Panel: 60W/100W/2x60W - 13.0/15.0/2x.14.0 lbs



PANEL SUPPORT BRACKETS

